



Highlights

- 4 Gigabits per second (Gbps) Fibre Channel (FC) interface technology
 - Start with a Direct Access Storage (DAS) configuration and seamlessly transition to a FC Storage Area Network (SAN) when ready
 - Easy to deploy and manage with the DS3000 Storage Manager
 - Combination of 12 Serial Attached SCSI (SAS) – up to 7.2 TB, or Serial Advanced Technology Attachmen (SATA) – up to 24.0 TB – drives per enclosure
 - Expandable to 28.8 TB with SAS, or up to 96.0 TB SATA with up to three EXP3000 enclosures
 - Flexible power options for Telco applications and Network Equipment Building System (NEBS) and European Telecommunication Standards Institute (ETSI) compliance.
-

IBM System Storage DS3400 Express

Cost-effective storage consolidation with a Fibre Channel direct-attach or SAN solution

As a business matures, so does the amount of data and the value of the data that it holds within the organisation. If the data is distributed across servers and individual storage systems, the business will face increased cost and complexity along with the accompanying business risks.

The IBM System Storage DS3400 Express leads the way for these organisations to take advantage of consolidating and sharing this data within a direct-attach or FC SAN solution. The DS3400 Express adds the most advanced front-end 4 Gbps FC technology to IBM time-proven designs for enterprise-class Redundant Array of Independent Disks (RAID) storage. With FC host connectivity and SAS back-end technology, the DS3400 Express is designed to improve productivity through data consolidation, availability, performance and scalability.

Easy to deploy and manage

The IBM System Storage DS3000 Storage Manager software is designed to provide a friendly user interface from setup to administration. This intuitive software builds on generations of IBM software development to provide trusted and reliable data management. Its task-based user interface significantly reduces the complexity of installation, configuration and management. The DS3000 Storage Manager approach is designed to enable even non-storage savvy administrators to quickly set up and deploy their storage solution.



Tiered storage solution

Tiered storage is the assignment of different categories of data to different types of drives in order to reduce total storage cost. A key attribute of the DS3000 Express series of disk systems is the integration of SAS and SATA technologies within a single enclosure. This simplifies purchasing and storage deployment with nearline applications using inexpensive SATA drives and highly-utilised applications deploying SAS drives.

Expand with multiple EXP3000s

The scalability of the DS3400 Express enables IT managers to respond to a constantly changing storage environment. By starting small, the DS3400 enables users to make additional investments in their infrastructure when data growth necessitates; thus organisations can easily increase capacity and storage capabilities with minimal cost and effort. The DS3400 Express capacity is increased by adding hard disk drives and by expanding the configuration and adding EXP3000 Express expansion units. Both of these operations can be performed without having to take the DS3400 Express off-line. This means 'zero-impact' to your environment and gives users control of their data storage as they expand capacity on an as-needed basis.

Flexible approach to storage

The DS3400 Express is a comprehensive storage solution for IBM System x, IBM System p, IBM BladeCenter and select third-party servers. This flexibility enables you to break free of server barriers and use a single storage solution in a mixed vendor environment. Also, because you do not have to sacrifice functionality for affordability, the DS3400 Express disk storage system can deliver powerful dynamic capabilities



that help you protect data. The disk storage system enables copy and disaster recovery (DR) features such as FlashCopy and VolumeCopy that can be enabled when required by your application.

Telco options

The IBM System Storage DS3400 Express includes a DC powered model that is especially suited for telco industry environments. The IBM System Storage DS3400 Express Model 42T, a NEBS-3 and ETSI compliant disk system and the IBM System Storage EXP3000 Express Model 02T storage expansion unit are both designed to be powered from a -48 V dc telco industry-standard power supply.

Priced right for small business

With the functionality and availability features that come standard and a price point that does not strain the budget, the DS3400 Express is the simple choice for small and medium businesses (SMBs) as well as larger organisations looking to support their departments and/or remote sites.

IBM System Storage DS3400 Express at a glance

Models	1726-41X – single controller 1726-42X – dual controller 1726-42T – dual controller Telco
RAID controller	Dual active
Cache per controller	512 MB battery-backed cache with 1 GB upgrade option
Host interface	Two host ports per controller, FC 4 Gbps auto-sensing 1 Gbps/2 Gbps
Drive interface	SAS
Supported drives	3 Gbps SAS: 146 GB, 300 GB and 450 GB SAS drives at 15,000 revolutions per minute (rpm) speeds 6 Gbps SAS: 300 GB, 450 GB, 600 GB SAS drives at 15,000 rpm speeds 3 Gbps SATA: 500 GB, 750 GB, 1.0 TB, 2.0 TB SATA drives at 7,200 rpm speed
RAID levels	RAID 0, -1, -3, -5, -6, -10
Storage partitions	4, 8, 16, 32
Maximum drives supported	48 SAS or SATA drives (using three EXP3000 Expansion Units)
Fans and power supplies	Dual-redundant, hot-swappable
Rack support	19" industry-standard rack
Management software	IBM System Storage DS3000 Storage Manager
SAN support	IBM supported FC switches
Warranty¹	Three-year parts and labour warranty
Size	Height: 8.7 cm (3.4 in.) Depth: 55.0 cm (21.6 in.) Width: 44.7 cm (17.6 in.) Weight: approximately 17.2 kg (38.0 lb) for a standard unit; when fully configured, 29.2 kg (64.5 lb)
Environment	Air temperature: – DS3400 on: 10° to 35°C (50.0° to 95°F); altitude: 30.5 (100 ft) below to 3000 m (9840 ft) above sea level; temperature change: 10°C (18°F) per hour – DS3400 off: 10° to 50°C (14.0° to 120.0°F); maximum altitude: 3000 m (9840 ft); temperature change: 15°C (27.0°F) per hour Humidity: – DS3400 on: 20 to 80 percent – DS3400 off: 10 to 90 percent – Maximum dew point: 26°C (79°F) – Maximum humidity gradient: 10 percent per hour
Heat output	Approximate heat output in British thermal units (Btu) per hour: – Minimum configuration: 205 Btu (60 watts) – Maximum configuration 1235 Btu (361 watts)
Supported systems	For a list of currently supported servers, operating systems, host bus adapters, clustering applications, SAN switches and directors, refer to the DS3000 series Interoperability Matrix available at ibm.com/systems/storage/disk/ds3000/ds3400/

For more information

To learn more about the [IBM System Storage DS3400 Express](#), please contact your IBM representative or IBM Business Partner or visit:

- ibm.com/systems/uk/storage/disk
- ibm.com/systems/uk/x
- ibm.com/systems/uk/bladecenter

Additionally, IBM Global Financing (IGF) can tailor financing solutions to your specific IT needs. For more information on great rates, flexible payment plans and loans, as well as asset buyback and disposal, visit:

ibm.com/financing/uk



IBM United Kingdom Limited

PO Box 41
North Harbour
Portsmouth
Hampshire
PO6 3AU
United Kingdom

IBM Ireland Limited

Oldbrook House
24-32 Pembroke Road
Dublin 4

IBM Ireland Limited registered in Ireland under company number 16226.

The IBM home page can be found at ibm.com

IBM, the IBM logo, ibm.com, BladeCenter, Express, FlashCopy, System p, System Storage and System x are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries.

A current list of IBM trademarks is available on the Web at 'Copyright and trademark information' at ibm.com/legal/copytrade.shtml

Other company, product and service names may be trademarks, or service marks of others.

References in this publication to IBM products, programs or services do not imply that IBM intends to make these available in all countries in which IBM operates.

Any reference to an IBM product, program or service is not intended to imply that only IBM products, programs or services may be used. Any functionally equivalent product, program or service may be used instead.

IBM hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, IBM warranty terms apply.

This publication is for general guidance only.

Information is subject to change without notice. Please contact your local IBM sales office or reseller for latest information on IBM products and services.

IBM does not provide legal, accounting or audit advice or represent or warrant that its products or services ensure compliance with laws. Clients are responsible for compliance with applicable securities laws and regulations, including national laws and regulations.

Photographs may show design models.

© Copyright IBM Corporation 2010
All Rights Reserved.



Please Recycle